



^All dimensions given are nominal and vary dependent on the chosen materials gauge and tensile

DESCRIPTION

Steelformers Ribline is a proprietary metal trapezoidal roofing and wall cladding system manufactured by long-run roll forming processes and installed with screw fasteners to supports. It can be formed from a variety of substrates to meet durability, formability and aesthetic requirements. This BPIS includes the profile, along with associated fasteners and flashings supplied by the manufacturer.

SCOPE OF USE

Generally used for roofing and wall cladding, mansards, ceilings, fences and decorative screens, or any other cladding application.

LIMITATIONS

There are limitations on the use of the product and compatibility with other building materials. Incompatible products in contact with or run-off from, may cause premature failure, and not reach the required performance. Refer to E2/AS1 Tables 21 and 22.

There are location limitations for the coated steel products. Refer to the coated metal product manufacturers for location limitations and maintenance requirements.

The minimum pitch allowance for Steelformers Ribline is 5°.

DESIGN

Design information is available from the NZMRM Code of Practice, at www.metalroofing.org.nz/cop. The Acceptable Solutions E2/AS1 and E2/AS4 also have design solutions for some residential building categories.



STEELFORMERS

TARANAKI STEELFORMERS LTD
WANGANUI STEELFORMERS KING COUNTRY LONGRUN

THE ROOF OVER TARANAKI'S HEAD SINCE '83

Head Office	3466 Mountain Road, Stratford	P. 0800 655 142	P. 06 765 5191	E: stratford@steelformers.co.nz
New Plymouth Branch	23 Katere Road, New Plymouth	P. 0800 476 634	P. 06 753 3831	E: npoffice@steelformers.co.nz
Wanganui Steelformers	380 Heads Road, Wanganui	P. 0800 800 077	P. 06 344 5142	E: chris@steelformers.co.nz
King Country Longrun	Huia Street, Taumarunui		P. 07 895 6464	E: blair@steelformers.co.nz

MATERIALS

1. Metallic coated grade G300/G550 steel complying with AS 1397 type AZ 150 coating
 2. Prepainted grade G300/G550 steel complying with AS 1397 coated in accordance to AS/NZS 2728 to Type 4 (Colorsteel Endura®/Colorcote® Zinacore™) or Type 6 (Colorsteel Maxx®/Colorcote® MagnaFlow™)
 3. Unpainted or Prepainted H34/H36 aluminium (Colorsteel Altimate®/Colorcote® Alumiguard™)
- Fasteners. 12 g screws coated to NZMRM Fastener Standard Class 5

INSTALLATION

Installation should be carried out by a suitably qualified practitioner in accordance with manufacturer's recommendations, the NZMRM Code of Practice, RANZ Metal Roofing and Wall Cladding Guide and for Residential housing E2/AS1 and E2/AS4.

Installers should take appropriate safety measures when working at height. For new residential construction, a Licensed Building Practitioner is required for the installation.

MAINTENANCE

Maintenance must be carried out in accordance with the manufacturer's recommendations.

New Zealand Steel: Refer to the "Residential Warranty, Environmental Categories, & Product Maintenance" brochure. Available for download at www.colorsteel.co.nz

Pacific Coil Coaters: Refer to the "Minimum Maintenance Schedule" brochure. Available from www.colorcote.co.nz

Unwashed areas must be regularly maintained to avoid the build-up of salt and debris.

COMPLIANCE WITH THE NEW ZEALAND BUILDING CODE (NZBC)

Steelformers Ribline and associated flashings made from equivalent material, used in combination with fasteners, underlays and clear sheeting accredited by NZMRM as complying to their product performance standards, will contribute to meeting the following performance requirements of the NZBC:

NZBC B1 Structure

Load/span testing and analysis in accordance with procedures described in Metal Roofing and Wall Cladding Code of Practice have led to the development of the following load span tables/charts.

Maximum spans for NZS3604 Wind Zones						
BMT	Tensile Strength	Wind Zone	Roofing		Wall Cladding	
			End	Internal	End	Internal
0.40mm	G550	Low/Medium	1000	1500	1250	1900
		High	750	1150	1000	1500
		Very High	550	850	750	1150
		Extra High	500	750	650	1000
0.55mm	G550	Low/Medium	1350	2000	1650	2500
		High	1150	1700	1400	2200
		Very High	950	1400	1200	1800
		Extra High	850	1250	1050	1600

Fastener requirements in accordance with NZS3604:2011, using 12g screws coated to NZMRM Fastener Standard Class 5.

	Roofing - rib fixed			Wall cladding - pan fixed	
	Steel based	Alu. based		Steel based	Alu. based
Timber	12x65 Timbertite®	12x65 stainless steel Timbertite® with profile washer and EPDM seal	Non-cavity	12x25 Timbertite®	12x25 Stainless Steel Timbertite®
			Cavity	Fixing must have min. penetration of 3x threads + height of rib. Ribline = 12x65 Timbertite®	Fixing must have min. penetration of 3x threads + height of rib. Ribline = 12x65 Stainless Steel Timbertite®
Steel up to 4.5mm	12x65 Steeltite®	12x65 Stainless Steel Steeltite® with profile washer and EPDM seal	Non-cavity	12x25 Steeltite®	12x25 Stainless Steel Steeltite®
			Cavity	Fixing must have min. penetration of 3x threads + height of rib. Ribline = 12x65 Steeltite®	Fixing must have min. penetration of 3x threads + height of rib. Ribline = 12x65 Stainless Steel Steeltite®

For buildings designed to AS/NZS 1170, refer to manufacturer.

NZBC B2 Durability

Sea Spray Exposure B (Low), C (Medium), D (High), E (Severe Marine)

Durability in accordance with Table 20 E2/AS1		
Product	Rain washed roofs	Walls and unwashed areas
Colorsteel Endura® / Colorcote® ZinaCore™	B, C, D	B, C
Colorsteel Maxx® / Colorcote® Magnaflow™	B, C, D, E	B, C, D
Colorsteel Altimate® / Colorcote® Alumigard™	B, C, D, E	B, C, D, E

NZBC C Fire

Colorsteel Endura®, Colorsteel Maxx®, Colorcote® ZinaCore™ and Colorcote® Magnaflow™ are rated as a Group 1-S material when tested in accordance with ISO 5660:2002 Part 2.

NZBC E1 Surface Water

Capacity Calculation in accordance with Metal Roofing and Wall Cladding Code of Practice calculators.

Minimum pitch 3°, rainfall intensity 150mm/hr		
Maximum Run	119.5m	
Catchment area of spreader	83m ²	- 20m run, 2 holes in spreader
Catchment behind penetration	38m ²	20m run, discharging each side of penetration

NZBC E2 External Moisture

Flashing details should be in accordance with Steelform Roofing Group design details, Metal Roofing and Wall Cladding Code of Practice, E2/AS1, or E2/AS4. Alternative details complying with the “4 D’s” (Deflection, Draining Drying and Durability) will also comply with the performance requirements of NZBC.

NZBC E3 Internal Moisture

When used with an absorbent, permeable underlay complying with NZS 2295:2006, or Dridex® pre-adhered fleece, Steelformers Ribline will contribute to compliance with NZBC E3.3.1. Ceiling spaces of sarked roofs, skillion roofs, barrel curved roofs, flat roofs and roofs over moisture laden environments must have provision for adequate ventilation.

NZBC F2 Hazardous Building Materials

Steelformers Ribline manufactured from metallic coated, prepainted metallic coated or pre-painted aluminium will meet the performance requirements of F2, 2.3.1.

NZBC G12 Water Supplies

Colorsteel and Colorcote® tested in accordance with AS/NZS 4020:2005 passed the requirements for products in contact with drinking water.

Product ban

Steelformers Ribline roofing and wall cladding products are not subject to any warnings or bans under the Building Act 2004.

**IN THE LONG RUN
IT PAYS TO GO WITH
THE LOCALS**

Because of Taranaki Steelformers policy of continuous product improvement, the company reserves the right, at any time and without notice to discontinue or modify designs, features and other specifications of their product. TSF reserves the right to either temporarily or permanently withdraw any such product from the market without incurring any liability. Taranaki Steelformers disclaim any liability for loss or damage suffered from the use of such material as all information is correct to the best of our knowledge at the time of printing. As this publication is only issued as a general guide it should not be treated as a substitute for detailed technical advice.